

## Uninterruptible Power Supply 1D1000B30C



The 1D1000B30C Uninterruptible Power Supply (UPS) provides a high quality output of 115v 60hz 1 $\phi$  @ 1000VA from an input of 115v 50/60hz. The integral valve regulated lead acid battery will support the output for 30 minutes in the event of an input supply failure.

The UPS is built into a fabricated steel container and is designed to be deck mounted on 'U'-bar using the fixing holes provided.

Access for maintenance and repair is from the front via a hinged cover that opens to the left.

Louvers pressed outwards from the front, sides & rear of the assembly, provide for fan assisted cooling during normal operation, and natural convection when the Anti Condensation Heaters are operating.

Electrical connections to and from the UPS are made via the top mounted removable gland plate,

The UPS can be provided with a battery monitoring option that continuously monitors the state of the batteries. An alarm is raised if there is a battery imbalance (due to a short circuit cell) or if there is a hydrogen concentration of >1%.

The 115V 60hz output is of high quality and is achieved by using a crystal controlled linear inverter with feedback loops that enable the control board to respond rapidly and smoothly to the demands of the output circuits. Closed loop operation reduces line and load regulation of the UPS output.

The built in battery charger will recharge a depleted battery to 80% charge in 8 hours.

## ELECTRICAL CHARACTERISTICS

### Input

115 volts single phase 60Hz in accordance with STANAG 1008 Edition 8

Option: ACH 115V or 230V

### Battery

Valve Regulated Sealed Lead Acid.  
2 parallel strings of 3 blocks connected in series.

Nominal voltage	36VDC
Autonomy time	30minutes,
Nominal rated capacity	48Ah.
Specified lifetime	7 to 10yrs at 20°C

Recommended normal operating temperature range is 20 to 25°C.  
Recharge to 80% from a fully discharged condition within 8 hours.

Option: Battery Monitoring : short circuit cell, hydrogen >1%

### Output

115V 1 phase, 60Hz, 1kVA unity power factor.

Waveform	Sinusoidal
THD	< 5%
Static voltage regulation	± 1%
Dynamic voltage regulation	± 5%
Frequency stability	± 0.1%.

### Protection

Input fuse protected. Output short circuit and over current protection.  
Over voltage, over temperature trips. Battery cut off at the end of discharge, battery overvoltage protection.

### Local Controls and Indications.

Supply ON/OFF selector switch, Supply available Lamp, Output On Lamp, ACH On Lamp (with ACH option), Battery Fault Lamp (with battery monitoring option)  
Meters for battery voltage, output voltage and output current.

### Remote Indications.

Volt -free contacts for Mains Fail, Output OK, Battery Fault (with battery monitoring option)

## MECHANICAL FEATURES

### Enclosure

Fabricated mild steel folded and welded for strength. Deck mounted with top steadies. Lifting eyes are provided.

### Dimensions

(O/A)(hxwx d) mm 872 x 570 x 340

Fixings (mm) 4 holes 13.0mm dia. Centres 495(w) x 227(d) mm  
Top steadies 2 holes 13.0mm dia. Centres 500 mm

**Weight** 150kg

### Cable Entry

Top via gland plate. Aperture 240mm x 127mm  
User connections are made to internal rail mounted terminals. Access for the cables is by a gland plate that can be drilled or punched as required for glands.

### Ingress Protection Rating

IP23

### Cooling

The UPS is designed for natural cooling by convection and louvres of sufficient size are provided for this purpose. The power assembly is fan cooled. A clearance of at least 100 mm should be allowed around the unit to allow proper ventilation.

### Maintenance

Front maintenance – Hinged door for access.

### Internal wiring

Low fire hazard cross linked polyolefin RADOX 125.

### Earth

For safety the chassis of the UPS must be earthed. An external M10 earth stud is situated adjacent to the gland plate.

## ENVIRONMENTAL CHARACTERISTICS

### Shock

The equipment is designed to meet a shock requirement of a maximum vertical acceleration (half sine-wave pulse) of amplitude 117.7m/s<sup>2</sup> (12g) and of duration 9ms (rise time to peak velocity) and 24ms (fall time to zero velocity). For installed shock levels in excess of this shock mounts should be fitted.

### Vibration

The unit, when 'hard' mounted, is designed to meet shipboard vibration. Typically: 5 to 33Hz +/- 0.125mm

### Noise

< 60dbA. @ 1m

### Electromagnetic Compatibility.

The equipment is designed to comply with the requirements of Def Stan 59-41. Emissions and susceptibility (Below deck limits)  
Inherently low emissions due to linear technology.

### Ambient Temperature.

0°C to + 45°C.

### Relative Humidity

10% to 95% non-condensing.

### Ships Motion

The equipment is designed to withstand, without damage or degradation of performance or spillage of fluids, ship motion due to the action of the sea and weather as well as accelerations and velocities deriving from deliberate ship manoeuvres. Typically:

Roll angles	± 30°
Pitch angles	± 10°
Steady list angles	± 15°
Steady trim angles	± 5°

