



## Features

- 100 W convection-cooled rating
- Small 5 x 3 x 1.07 inches form factor
- 6.7 W/in<sup>3</sup> power density
- High efficiency > 85%
- Low conducted and radiated noise
- Power good and power fail signal
- Cover kit accessory available

## Electrical Specifications

AC Input	90–264 V, Universal	
Input Frequency	47–63 Hz	
Input Current	120 VAC: 2.0 A max.	230 VAC: 1.0 A max.
Inrush Current	120 VAC: 18 A max.	230 VAC: 35 A max.
Leakage Current	120 VAC: < 500 $\mu$ A	230 VAC: < 1000 $\mu$ A
Efficiency	120 VAC: 83% typical	230 VAC: 85% typical
Hold-up Time	120 VAC: 10 ms	230 VAC: 16 ms
Output Power	100 W	
Line Regulation	+/-0.3%	
Load Regulation <sup>1</sup>	V1: +/-1%; V2, V3 and V4: +/-5%	
Transient Response	10%, 50% to 100% load change, 50/60 Hz, 50% duty cycle, 0.1 A/ $\mu$ s, recovery time < 5 ms	
Rise Time	< 50 ms	
Set Point Tolerance	V1: +/-2%; V2, V3, V4: +/-5%	
Over Current Protection	110 to 170%	
Over Voltage Protection	6.2 V +/-0.4 V for 5 V	
Short Circuit Protection	Short term, autorecovery	
Switching Frequency	Boost converter: 45 kHz typical Resonant converter: 45 kHz typical	
Operating Temperature	0 to 70°C, refer derating curve	
Storage Temperature	-40 to +85°C	
Relative Humidity	95% Rh, noncondensing	
Altitude	Operating: 10,000 ft.; Nonoperating: 40,000 ft.	
MTBF	1.02m Hours, Telcordia SR332 Issue-3	
Isolation Voltage	Min. 4242 VDC between input to output	
Cooling	Convection	

Model Number	Voltage	Max. Load <sup>2</sup>	Min. Load	Ripple <sup>3</sup>
LFVLT100-1001	V1=12 V	7.5 A	1.0 A	3%
LFVLT100-1002	V1=15 V	6.67 A	0.5 A	3%
LFVLT100-1003	V1=24 V	4.2 A	0.1 A	1.5%
LFVLT100-1004	V1=48 V	2.1 A	0.2 A	1.04%
LFVLT100-4000	V1=5.1 V, V2=12.25 V, V3=-5 V, V4=-12 V	V1=12.0 A, V2=4.0 A, V3=0.8 A, V4=0.8 A	V1=3.0 A, V2=0.1 A, V3=0.0 A, V4=0.0 A	V1, V2=1.5% V3=2%, V4=1.25%
LFVLT100-4001	V1=5.1 V, V2=24.5 V, V3=12 V, V4=-12 V	V1=12.0 A, V2=2.0 A, V3=0.8 A, V4=0.8 A	V1=3.0 A, V2=0.1 A, V3=0.0 A, V4=0.0 A	1%
LFVLT100-4002	V1=5.1 V, V2=16 V, V3=-4.8 V, V4=-15.5 V	V1=12.0 A, V2=3.0 A, V3=0.8 A, V4=0.8 A	V1=3.0 A, V2=0.1 A, V3=0.0 A, V4=0.0 A	V1, V2, V4=1% V3=2%
LFVLT100-4003	V1=5.1 V, V2=12 V, V3=24 V, V4=-12 V	V1=12.0 A, V2=4.0 A, V3=0.8 A, V4=0.8 A	V1=3.0 A, V2=0.1 A, V3=0.0 A, V4=0.0 A	1%
LFVLT80-CK metal cover kit accessory				

Connectors		
J1	Pin 1	AC NEUTRAL
	Pin 2	AC LINE
Spade Connector		EARTH
J2	Pin 1, 2, 3, 4	V1
	Pin 5, 6, 7, 8	RTN
	Pin 9, 10	V2
	Pin 11	V3
	Pin 12	V4
J3	Pin 1	RTN
	Pin 2	POWER FAIL/GOOD

## Notes

1. Single output models: +/-2.5% for 12 V, +/-3% for 15 and 24 V, +/-2% for 48 V.  
Quad output models : +/-1% for V1; +/-5% for V2, V3, V4.
2. Maximum current per output channel. Do not exceed total output power rating.
3. Ripple is peak to peak with 20 MHz bandwidth and 10 µF (Tantalum capacitor) in parallel with a 0.1 µF capacitor at rated line voltage and load ranges.
4. Power fail and power good signal on quad output models only.
5. Specifications are for nominal input voltage, 25°C and max. load unless otherwise stated.
6. Derate output power linearly to 80% from 90 VAC to 80 VAC input.



Innovations in Power

### Mechanical Specifications

AC Input Connector (J1)	Molex: 26-60-4030 or equivalent Mating: 09-50-3031; Pins: 08-50-0106
EARTH	Molex: 19705-4301 Mating: 190030001
DC Output Connector (J2)	Tyco: 1-640445-2 or equivalent Mating: 1-647402-2; Pins: 3-647409-1
Signal Connector (J3)	Molex: 22-23-2021 or equivalent Mating: 22-01-2021
Dimensions	5.0 x 3.04 x 1.07 inches (127.0 x 77.22 x 27.18 mm)
Weight	250 g

### EMC

CE Mark	Complies with LVD Directive
Conducted Emissions	EN55022-B, CISPR22-B, FCC PART15-B, EN50082-1
Static Discharge	EN61000-4-2, Level-3
RF Field Susceptibility	EN61000-4-3, Level-3
Fast Transients/Bursts	EN61000-4-4, Level-3
Radiated Emissions	EN55022-B, CISPR22-B, FCC PART15-B To be controlled in end system
Surge Susceptibility	EN61000-4-5, Level-3
Harmonic current	EN61000-3-2, Class A

### Safety

Safety Standard(s)	IEC60950-1 (ed.2), EN60950-1, UL60950-1 (2nd Edition), CSA C22.2 No. 60950-1 (2nd Edition), Class 1 SELV
Approval Agency	Nemko, UL, C-UL
Safety File Number(s)	Nemko: P09210934 UL: E150565

### Signal

Power Fail/Good Signal <sup>4</sup>	Signal goes high after a delay of 100 ms once main output is within regulation band. Signal goes low 1.5 ms advance before output goes out of regulation due to mains failure
-------------------------------------	--

