



30kVA Uninterruptible Power Supply 3RPQ30KA



The 3RPQ30KA Uninterruptible Power Supply (UPS) supplies 230V, 60Hz three phase output to ships loads. The UPS consists of a transformer isolated rectifier, an inverter and static switch. An external battery cabinet is also required.

The rectifier in the UPS is supplied by the ship's 440V 3phase 60Hz supply and provides power to supply the inverter and recharge the battery.

In normal operation, the rectifier float charges the battery and supplies the DC input to the inverter. The inverter supplies the output. When the input supply fails the battery supplies the DC input to the inverter that continues to supply the output. When the mains returns the rectifier recharges the battery.

As required for naval applications the UPS is designed to meet the necessary ruggedness in terms of shock, vibration and EMC requirements.

The unit is designed for front operation and maintenance and has an ingress protection rating of IP23.

Gresham Power Electronics
Gresham House, Telford Road
Salisbury, SP2 7PH, UK
+44 (0)1722 413060
www.greshampower.com
e-mail: sales@greshampower.com



ELECTRICAL CHARACTERISTICS

Input

440 volts 3 phase 3 wire 60Hz in accordance with STANAG 1008 Edition 8

Input Rated Voltage	440V
Input Current THD	<4%
Power Factor	0.99
Inrush Current	<Inom

Note: input current is dependent on the recharge current required by the battery.

Option: Alternative input supply
Option: ACH 115V or 230V

Battery input

Suitable for Valve Regulated Sealed Lead Acid type,
Nominal voltage 768VDC.
Nominal charge current 0.1C

Output

230V 3 phase, 60Hz, 30kVA, 24kW

Waveform	Sinusoidal
THD	<2%
Static voltage regulation	± 1%
Dynamic voltage regulation	± 5%
Frequency stability	± 0.1%.

Options

Earth isolation monitor
Output distribution
Auxiliary 24V DC Output
Individual Battery monitoring
Alternative output voltages 440V,415V, 230V or 115V

Efficiency >90 %

Protection

Input circuit breaker. Output short circuit and over current protection. Over voltage and over temperature trips are also provided to afford general protection to the unit. Battery cut off at the end of discharge, battery overvoltage protection.

Local Controls and Indications.

Supply ON/OFF selector switch, Supply available LED, Rectifier LED Battery LED, Inverter LED, Liquid Crystal Display with scroll pushbuttons to view the parameters

Remote Indications.

RS232 interface gives status/fault information plus the parameter values of supply voltage, supply current, Output Voltage, Output Current, Battery Voltage, Battery charge/discharge current, Temperature, Battery Capacity

MECHANICAL FEATURES

Enclosure

Fabricated mild steel folded and welded for strength. Deck mounted with top steadies. Lifting eyes are provided.

Dimensions

2105 x 1600 x 725 (O/A)(h x w x d) mm

A clearance of at least 100 mm should be allowed around the unit (including base) to allow proper ventilation.

Weight 810kg

Cable Entry

User connections are made to internal rail mounted and stud terminals. Access for the cables is by a gland plate that can be drilled or punched as required for glands.

Ingress Protection Rating

IP44

Cooling

The UPS is designed for natural cooling by convection and vents of sufficient size are provided for this purpose. Individual cooling fans for power assemblies are provided. Unrestricted airflow should be allowed around the unit.

Maintenance

Front maintenance – Lift off hinged doors for access.

Internal wiring

Low fire hazard cross linked polyolefin RADOX 125.

Earth

For safety the chassis of the UPS must be earthed. An external M10 earth stud is situated adjacent to the gland plate.

ENVIRONMENTAL CHARACTERISTICS

Shock

The equipment is designed to meet a shock requirement of 15g (half sine-wave pulse). For installed shock levels in excess of this shock mounts should be fitted.

Vibration

The unit is designed to meet shipboard vibration requirements. Typically: 5 to 33Hz +/- 0.125mm

Noise

< 65dbA. @ 1m

Electromagnetic Compatibility.

The equipment is designed to comply with the requirements of Def Stan 59-411. Emissions and susceptibility (Below deck limits)

Ambient Temperature.

0°C to + 45°C.

Relative Humidity

10% to 95% non-condensing.

Ships Motion

The equipment is designed to withstand, without damage or degradation of performance or spillage of fluids, ship motion due to the action of the sea and weather as well as accelerations and velocities deriving from deliberate ship manoeuvres. Typically:

Roll angles	± 30°
Pitch angles	± 10°
Steady list angles	± 15°
Steady trim angles	± 5°



Gresham Power Electronics
Gresham House, Telford Road
Salisbury, SP2 7PH, UK
+44 (0)1722 413060
www.greshampower.com
e-mail: sales@greshampower.com

